

Compact Excavators / E60 Compact Excavator

E60 Excavator Specifications & Options

Check out detailed specs for the E60 compact excavator.

Standard Optional **N/A** Not Applicable

Units **US**

Bobcat E60 R2-Series

Configuration

E60 R2 Long Arm

E60 R2 Extendable Arm

Engine

Emissions Tier (EPA)	Tier 4	Tier 4
Engine Fuel	Diesel	
Maximum Governed RPM	2,200 rpm	2,200 rpm
Horsepower	55 hp	55 hp
Turbocharged Engine	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Optional Horsepower	n/a	

Performance

Operating Weight	12,315 lb	12,646 lb
Weight Class	6 t	6 t
Travel Speed - High	2.8 mph	2.8 mph
Travel Speed - Low	1.8 mph	1.8 mph
Arm Digging Force	6,446 lbf	7,104 lbf
Bucket Digging Force	10,261 lbf	10,261 lbf
Rated Lift Capacity	6411 lb	6345 lb
Lift Radius	118 in	
Boom Swing - Left	75°	
Boom Swing - Right	50°	
Maximum Dig Depth	13.1 ft	14.8 ft
Max Dump Height	14.3 ft	15.2 ft
Maximum Reach at Ground Level	20.5 ft	22.1 ft

Capacities

Fuel Tank	19 gal	
-----------	--------	--

Hydraulic System

Auxiliary Std Flow	20 gal/min	
Auxiliary Pressure	3,045 psi	3,045 psi

Dimension

Length	218.3 in	218.3 in
Overall Length in Travel Position	218.3 in	218.3 in
Width	77.2 in	77.2 in
Height	100.1 in	100.1 in
Height with Operator Cab	100.1 in	100.1 in

Features

Air Conditioning	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Cab Enclosure	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Cab Heater	N/A	N/A
Heater Air Conditioning	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Radio	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Tail Swing Type	Conventional	Conventional
Engine Shutdown	<input type="checkbox"/>	<input type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>	<input type="checkbox"/>
Secondary Auxiliary Hydraulics	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Quick Tach System	<input type="checkbox"/>	<input type="checkbox"/>
Rubber Track	<input type="checkbox"/>	<input type="checkbox"/>
Selectable Auxiliary Hydraulic Flow	<input type="checkbox"/>	<input type="checkbox"/>
Angle Blade	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.